

PRODUCT DESCRIPTION:

The area light is mostly used for industrial and commercial applications such as road and area lighting, parking decks, auto dealerships, high masts, housing complexes, shopping malls, sporting complexes and fields, parks and recreational areas and municipal lots.

FEATURES:

- Mercury Free
- No UV
- Flexible, modular design
- Easy Installation
- Daylight Sensor available
- Nichia SMD chip
- Beam Angle Type 2 / 3 / 4 / 5 or 90°
- IP65 waterproof grade
- Processed by painting and anodic oxidation treatment, shock resistant and anti-corrosion

DIMENSIONS:

Area Light 100W Spec

LOD-MAAL-100W-50K-TPIII-SBA

LOD-MAAL-100W-57K-TPIII-SBA



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-MAAL-100W-50K-TPIII-SBA	LOD-MAAL-100W-57K-TPIII-SBA
Input Wattage (W)	100W	
Lumens Delivered (LM)	14,081.7LM	14,221.2LM
Efficacy (LM/W)	141.61LM/W	143.01LM/W
CRI	70	
Lifespan	50,000 hours	
Color Temperature	5,000K	5,700K
Wattage Equivalent	250W	
Dimmable	Yes	
IP Rating	IP65	
Beam Angle	Type 2 / 3 / 4 / 5 or 90°	
Input Voltage	AC100-277V	
Power Factor	0.9	
Housing	Die Cast Aluminum	
Lens	Clear	
Mounting	Pole Mount	
THD	20%	
Size		
Certification	DLC, ETL	
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
Environment	Outdoor	
Warranty	5 years limited	

Special Order: 4,000K / 5,700K



OPTIONAL ACCESSORIES:



Slip fitter



Bracket



Extruded Arm



Daylight Sensor

