

PRODUCT DESCRIPTION:

Industrial and commercial applications. For road and area lighting such as parking decks, auto dealerships, high masts, apartments, residential complexes, shopping malls, sporting complexes and fields, educational facilities, streets, roadways, parks, recreational bike paths, and municipal lots.

FEATURES:

- Philips Lumileds 3030 LED chips
- Heavy duty die-cast aluminum housing with quick mount back plate for easy installation
- fully sealed with an IP rating of 65
- High quality tempered glass optics
- Integral secondary heat sink to optimize thermal transfer and maximize performance and life of LED
- Driver is mounted in direct contact with the casting for low operating temperature and long life.
- Polyester powder-coated finish, rust and corrosion proof; stabilized to extreme climate changes without cracking or peeling

DIMENSIONS:

40W Wall Pack

LOD-WP-40WSAD40K-HLV2



SPECIFICATIONS:

| SPECIFICATION | Details |
|-----------------------|-------------------------------|
| Model | LOD-WP-40WSAD40K-HLV2 |
| Input Wattage (W) | 40W |
| Lumens Delivered (LM) | 4,782.5LM |
| Efficacy (LM/W) | 123.87LM/W |
| CRI | 71.1 |
| Lifespan | 50,000 hours |
| Color Temperature | 4,000K |
| Wattage Equivalent | 70W – 175W HID |
| Dimmable | No |
| IP Rating | IP65 |
| Beam Angle | 120 |
| Input Voltage | AC120-277V |
| Power Factor | 0.932 |
| Housing | Aluminum |
| Lens | Frosted |
| THD | 8.6% |
| Mounting | Wall Surface |
| Weight (LBS) | 7.716lbs |
| Size | 14.3" x 9.2" x 7.52" |
| Certification | DLC, ETL |
| Operating Temperature | -20°C to 50°C (-4°F to 122°F) |
| Environment | Outdoor |
| Warranty | 5 years limited |

4,000K is special order only

OPTIONAL ACCESSORIES:

Cut off shield

CONTROLS:

Photocell optional

Motion sensor optional

