

LEDone®

LOD-MSL-WP Series Installation

SAFETY INSTRUCTIONS: Read instructions carefully before attempting to install fixture.

- All wiring should be performed by a qualified electrician.
- Disconnect power before installing or servicing. This fixture must be wired in accordance with the National Electrical Code and applicable local codes and ordinances.
- Proper grounding is required to ensure personal safety.

CAUTION: Risk of fire

- **WARNING:** Make certain power is OFF before installing or maintaining fixture. No user serviceable parts inside.
- **WARNING:** Luminaire must be connected to a wiring system with an equipment- grounding conductor.
- **WARNING:** Please check if the voltage marked on the luminaire is consistent with the input voltage to be connected.
- **WARNING:** Do NOT operate in ambient temperatures above those indicated on the luminaire template.
- **WARNING:** Avoid use in environments containing sulfur, chlorine or other halides such as methyl acetate, ethyl acetate, cyanoacrylates, glycol ethers, formaldehyde or butadiene.

CLEANING & MAINTENANCE:

CAUTION: Be sure the fixture temperature is cool enough to touch. Do NOT clean or maintain while the fixture is energized.

1. Clean glass lens with non-abrasive glass cleaning solution.
2. Do NOT open fixture to clean the LED. Do NOT touch the LED.

Note: These instructions do not cover all details or variation in equipment, nor do they provide for every possible situation during installation, operation or maintenance.

INSTALLATION (Wall Mounting):

1. Fix bracket onto the wall.
2. Fix the fixture on the bracket with the bolt.
3. Connect supply wires to luminaire wire leads per the wiring diagram.

