


# LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.2V I:0.1551A P:17.68W PF:0.9484 Lamp Flux:2576.84x1 lm		
NAME: LOC-14TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1155*95	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 145.76 lm/W			
MODEL		Imax(cd)	877.0	S/MH(C0/180)	1.23
NOMINAL POWER(W)	19	LOR(%)	100.0	S/MH(C90/270)	1.34
RATED VOLTAGE(V)	120-277	TOTAL FLUX(lm)	2576.8	$\eta$ UP,DN(C0-180)	0.0,45.4
NOMINAL FLUX(lm)	2576.84	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,54.6
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	$\eta$ down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature:25DEG  
 Operators:  
 Test Date:2020-05-15

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
 Humidity:50%  
 Test Distance:8.600m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
5	871.4	857.6	853.8	858.8	873.0	868.6	867.8	867.6	0- 5	20.78	20.78	0.81,0.81
10	856.4	833.8	830.6	836.0	859.6	855.7	858.7	853.6	5- 10	61.18	81.95	3.18,3.18
15	832.2	805.7	807.5	809.0	837.2	838.3	849.6	835.2	10- 15	99.16	181.1	7.03,7.03
20	799.8	774.0	784.3	778.3	806.4	816.9	840.4	813.0	15- 20	133.9	315.0	12.2,12.2
25	759.6	739.0	761.2	744.0	767.4	791.7	831.3	787.1	20- 25	164.6	479.6	18.6,18.6
30	712.9	701.6	712.0	707.4	721.7	763.7	792.1	758.6	25- 30	190.0	669.6	26,26
35	660.3	656.0	662.8	662.5	670.1	726.3	752.9	720.7	30- 35	208.2	877.8	34.1,34.1
40	603.2	596.5	613.7	603.2	613.5	672.5	713.7	666.4	35- 40	219.5	1097	42.6,42.6
45	542.5	537.0	564.5	543.7	553.1	618.5	674.5	611.9	40- 45	224.3	1322	51.3,51.3
50	479.0	477.9	515.3	484.5	490.0	564.8	635.3	557.8	45- 50	223.0	1545	59.9,59.9
55	414.4	420.2	435.8	426.5	424.6	512.2	573.0	504.8	50- 55	215.0	1760	68.3,68.3
60	348.9	361.2	356.4	366.6	358.4	458.7	510.6	451.1	55- 60	199.0	1959	76,76
65	283.9	285.5	276.9	288.2	292.4	391.3	448.3	384.0	60- 65	176.9	2136	82.9,82.9
70	219.7	212.9	197.5	212.6	225.7	326.6	386.0	319.8	65- 70	150.1	2286	88.7,88.7
75	158.1	142.9	118.0	139.4	163.0	264.8	323.6	258.5	70- 75	120.0	2406	93.4,93.4
80	99.08	79.72	82.37	73.80	103.6	201.7	230.8	196.2	75- 80	88.28	2494	96.8,96.8
85	45.65	45.17	46.75	42.03	48.89	117.9	137.9	113.5	80- 85	56.81	2551	99,99
90	6.988	11.05	11.14	10.78	11.25	35.52	45.11	32.25	85- 90	26.16	2577	100,100
95									90- 95			
100									95-100			
105									100-105			
110									105-110			
115									110-115			
120									115-120			
125									120-125			
130									125-130			
135									130-135			
140									135-140			
145									140-145			
150									145-150			
155									150-155			
160									155-160			
165									160-165			
170									165-170			
175									170-175			
180									175-180			
DEG	LUMINOUS INTENSITY:cd								UNIT:lm			

C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature:25DEG  
 Operators:  
 Test Date:2020-05-15

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
 Humidity:50%  
 Test Distance:8.600m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
p <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.03	.98	.94	1.01	.96	.93	.96	.93	.90	.92	.89	.87	.89	.86	.84	.82
2.0	.89	.82	.76	.87	.81	.75	.84	.78	.73	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.69	.63	.76	.68	.62	.73	.67	.61	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.53	.68	.59	.52	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.61	.52	.45	.60	.52	.45	.58	.50	.45	.56	.49	.44	.54	.48	.44	.41
6.0	.55	.46	.40	.54	.46	.39	.52	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.35	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25DEG  
Operators:  
Test Date: 2020-05-15

γ Range: 0 - 90DEG  
γ Interval: 0.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
Humidity: 50%  
Test Distance: 8.600m [K=1.0000]  
Remarks:

## WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.330	.188	.060	.323	.184	.059	.310	.178	.057	.298	.172	.055	.286	.166	.053															
2.0	.305	.167	.051	.298	.164	.051	.286	.159	.049	.276	.155	.048	.265	.150	.047															
3.0	.279	.148	.044	.273	.146	.044	.263	.142	.043	.253	.139	.043	.244	.135	.042															
4.0	.256	.133	.039	.251	.131	.039	.242	.128	.038	.233	.125	.038	.225	.122	.037															
5.0	.235	.120	.035	.231	.119	.035	.223	.116	.034	.215	.114	.034	.208	.111	.033															
6.0	.218	.109	.031	.214	.108	.031	.206	.106	.031	.200	.104	.030	.193	.102	.030															
7.0	.202	.100	.028	.199	.099	.028	.192	.097	.028	.186	.095	.028	.180	.094	.028															
8.0	.188	.092	.026	.185	.091	.026	.179	.090	.026	.174	.088	.025	.169	.087	.025															
9.0	.176	.085	.024	.173	.085	.024	.168	.083	.024	.163	.082	.023	.159	.081	.023															
10.0	.165	.079	.022	.163	.079	.022	.158	.077	.022	.154	.076	.022	.150	.075	.022															

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.182	.156	.133	.155	.134	.114	.106	.092	.079	.061	.053	.046	.020	.017	.015		
2.0	.174	.132	.096	.149	.113	.083	.102	.079	.058	.059	.046	.034	.019	.015	.011		
3.0	.166	.114	.073	.142	.099	.063	.098	.069	.044	.056	.040	.026	.018	.013	.009		
4.0	.158	.101	.057	.136	.087	.050	.094	.061	.035	.054	.036	.021	.017	.012	.007		
5.0	.151	.091	.046	.130	.079	.040	.089	.055	.029	.052	.032	.017	.017	.011	.006		
6.0	.144	.082	.039	.123	.071	.034	.085	.050	.024	.049	.029	.014	.016	.010	.005		
7.0	.137	.076	.033	.118	.065	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004		
8.0	.130	.070	.028	.112	.061	.025	.077	.042	.018	.045	.025	.010	.015	.008	.003		
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003		
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003		

C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature:25DEG  
 Operators:  
 Test Date:2020-05-15

γ Range: 0 - 90DEG  
 γ Interval: 0.5DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
 Humidity:50%  
 Test Distance:8.600m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	18.9	20.4	19.1	20.6	20.8	19.2	20.8	19.5	21.0	21.2
3H	20.3	21.8	20.6	22.0	22.3	20.5	21.9	20.8	22.2	22.4
4H	20.9	22.3	21.3	22.6	22.8	20.9	22.2	21.2	22.5	22.8
6H	21.4	22.7	21.8	23.0	23.3	21.2	22.5	21.5	22.7	23.0
8H	21.6	22.8	21.9	23.1	23.4	21.3	22.6	21.7	22.9	23.2
12H	21.7	22.9	22.0	23.2	23.5	21.4	22.6	21.8	22.9	23.3
4H 2H	19.5	20.9	19.8	21.1	21.4	19.8	21.1	20.1	21.4	21.6
3H	21.2	22.4	21.5	22.7	23.0	21.2	22.4	21.6	22.7	23.0
4H	21.9	23.0	22.3	23.3	23.7	21.7	22.8	22.1	23.1	23.5
6H	22.5	23.5	22.9	23.8	24.2	22.1	23.1	22.5	23.5	23.8
8H	22.7	23.6	23.1	24.0	24.4	22.3	23.3	22.8	23.6	24.0
12H	22.9	23.7	23.3	24.1	24.5	22.5	23.4	23.0	23.8	24.2
8H 4H	22.1	23.1	22.5	23.4	23.8	21.9	22.9	22.4	23.2	23.6
6H	22.9	23.6	23.3	24.0	24.5	22.5	23.3	23.0	23.7	24.1
8H	23.2	23.8	23.6	24.3	24.7	22.8	23.5	23.3	23.9	24.4
12H	23.4	24.0	23.9	24.4	24.9	23.1	23.7	23.6	24.2	24.6
12H 4H	22.1	23.0	22.6	23.4	23.8	21.9	22.8	22.4	23.2	23.6
6H	22.9	23.6	23.4	24.0	24.5	22.6	23.3	23.0	23.7	24.1
8H	23.2	23.8	23.7	24.3	24.8	22.9	23.5	23.4	24.0	24.5
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.1					+ 0.2 / - 0.2				
1.5H	+ 0.1 / - 0.2					+ 0.3 / - 0.4				
2.0H	+ 0.1 / - 0.2					+ 0.3 / - 0.3				

CIE Pub.117 Corrected 2577 lm Total Lamp Luminous Flux. (8log(F/F0) = 3.3)

C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature: 25DEG  
 Operators:  
 Test Date: 2020-05-15

γ Range: 0 - 90DEG  
 γ Interval: 0.5DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
 Humidity: 50%  
 Test Distance: 8.600m [K=1.0000]  
 Remarks:

## UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	37	55	44	37	31
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	55	71	64	55	48
1.25	82	71	63	80	70	63	78	69	62	55
1.50	87	76	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	68
2.50	98	90	83	96	88	82	92	85	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	94	103	97	93	99	94	90	81
5.00	108	103	98	105	101	97	101	97	94	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature: 25DEG  
 Operators:  
 Test Date: 2020-05-15

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
 Humidity: 50%  
 Test Distance: 8.600m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Conical surface Flux(90deg):

1321.6 lm

%lum = 51.3%


%lamp = 51.3%

Conical surface Flux(120deg):

1958.7 lm

%lum = 76.0%


%lamp = 76.0%



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:25DEG  
Operators:  
Test Date:2020-05-15

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
Humidity:50%  
Test Distance:8.600m [K=1.0000]  
Remarks:


AAI Figure



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



ISOLUX DIAGRAM



C Range: 0 - 360DEG	γ Range: 0 - 90DEG
C Interval: 5.0DEG	γ Interval: 0.5DEG
Test Speed: HIGH	Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Temperature:25DEG	Humidity:50%
Operators:	Test Distance:8.600m [K=1.0000]
Test Date:2020-05-15	Remarks:

## LED Avg.L Report

Test:U:120.2V I:0.1551A P:17.68W PF:0.9484 Lamp Flux:2576.84x1 lm		
NAME: LOC-14TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1155*95	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180 (65) av	6215
L_0~180 (75) av	5654
L_0~180 (85) av	4944
L_90~270 (65) av	7821
L_90~270 (75) av	7777
L_90~270 (85) av	9659
L_45 (65) av	7274
L_45 (75) av	7093
L_45 (85) av	8330

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature:25DEG  
 Operators:  
 Test Date:2020-05-15

γ Range: 0 - 90DEG  
 γ Interval: 0.5DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
 Humidity:50%  
 Test Distance:8.600m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25DEG  
Operators:  
Test Date: 2020-05-15

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.290  
Humidity: 50%  
Test Distance: 8.600m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25DEG  
Operators:  
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

## LUMINOUS DISTRIBUTION INTENSITY DATA

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25DEG  
Operators:  
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

## LUMINOUS DISTRIBUTION INTENSITY DATA

Table--3

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25DEG  
Operators:  
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

## LUMINOUS DISTRIBUTION INTENSITY DATA

Table--4

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:25DEG  
Operators:  
Test Date:2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```