


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.2V I:0.1851A P:22.09W PF:0.9930 Lamp Flux:3337.7x1 lm		
NAME: LOC-14TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1155*95	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 151.10 lm/W			
MODEL		Imax(cd)	1128	S/MH(C0/180)	1.23
NOMINAL POWER(W)	24	LOR(%)	100.0	S/MH(C90/270)	1.35
RATED VOLTAGE(V)	120-277	TOTAL FLUX(lm)	3337.7	η UP,DN(C0-180)	0.0,44.9
NOMINAL FLUX(lm)	3337.7	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,55.1
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
5	1121	1102	1097	1104	1124	1119	1118	1117	0- 5	26.73	26.73	0.80,0.80
10	1101	1071	1066	1075	1107	1104	1108	1100	5- 10	78.72	105.4	3.16,3.16
15	1070	1033	1035	1039	1079	1083	1097	1077	10- 15	127.6	233.1	6.98,6.98
20	1028	991.6	1004	999.3	1039	1056	1087	1049	15- 20	172.3	405.3	12.1,12.1
25	975.9	945.7	973.4	954.8	990.0	1025	1077	1016	20- 25	211.9	617.2	18.5,18.5
30	915.4	896.7	909.9	907.0	931.5	990.7	1027	980.2	25- 30	244.7	861.9	25.8,25.8
35	847.9	837.6	846.3	848.7	865.2	943.5	978.2	932.2	30- 35	268.1	1130	33.9,33.9
40	774.2	761.2	782.8	772.4	792.6	875.1	929.0	862.8	35- 40	282.9	1413	42.3,42.3
45	696.4	684.7	719.2	695.6	715.0	806.3	879.8	793.2	40- 45	289.2	1702	51,51
50	615.0	609.0	655.7	619.3	633.6	737.9	830.7	724.2	45- 50	287.7	1990	59.6,59.6
55	531.7	535.0	556.0	544.2	549.3	670.7	751.5	656.8	50- 55	277.6	2267	67.9,67.9
60	447.8	459.5	456.4	467.2	464.0	602.4	672.4	588.3	55- 60	257.3	2525	75.6,75.6
65	363.9	364.3	356.7	368.6	378.6	516.3	593.2	502.5	60- 65	229.4	2754	82.5,82.5
70	281.8	272.9	257.0	273.4	294.5	433.5	514.1	420.6	65- 70	195.5	2950	88.4,88.4
75	202.3	184.9	157.3	181.5	211.8	354.6	434.9	342.5	70- 75	157.4	3107	93.1,93.1
80	127.4	105.3	109.7	98.70	135.0	274.1	315.8	262.7	75- 80	117.1	3224	96.6,96.6
85	57.70	59.43	62.00	55.94	64.29	167.5	196.7	155.5	80- 85	76.63	3301	98.9,98.9
90	9.039	14.21	14.33	13.92	14.50	62.94	77.54	50.32	85- 90	37.00	3338	100,100
95									90- 95			
100									95-100			
105									100-105			
110									105-110			
115									110-115			
120									115-120			
125									120-125			
130									125-130			
135									130-135			
140									135-140			
145									140-145			
150									145-150			
155									150-155			
160									155-160			
165									160-165			
170									165-170			
175									170-175			
180									175-180			
DEG	LUMINOUS INTENSITY:cd								UNIT:lm			

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.03	.98	.94	1.00	.96	.92	.96	.93	.89	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.76	.87	.80	.75	.83	.78	.73	.80	.75	.71	.77	.73	.70	.67
3.0	.78	.69	.62	.76	.68	.62	.73	.66	.61	.70	.65	.60	.68	.63	.59	.56
4.0	.69	.60	.53	.67	.59	.52	.65	.57	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.61	.52	.45	.60	.51	.45	.58	.50	.44	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.39	.54	.45	.39	.52	.45	.39	.51	.44	.38	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.45	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.33	.27	.39	.32	.27	.38	.32	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.333	.189	.060	.326	.186	.059	.313	.179	.057	.300	.173	.056	.289	.167	.054	
2.0	.306	.168	.051	.300	.165	.051	.288	.160	.050	.277	.156	.049	.267	.151	.048	
3.0	.280	.149	.045	.275	.147	.044	.264	.143	.043	.254	.139	.043	.245	.136	.042	
4.0	.257	.133	.039	.252	.132	.039	.242	.129	.038	.234	.126	.038	.226	.123	.037	
5.0	.236	.120	.035	.232	.119	.035	.223	.116	.034	.216	.114	.034	.209	.111	.033	
6.0	.218	.109	.031	.214	.108	.031	.207	.106	.031	.200	.104	.031	.194	.102	.030	
7.0	.202	.100	.028	.199	.099	.028	.192	.097	.028	.186	.095	.028	.180	.094	.028	
8.0	.189	.092	.026	.186	.091	.026	.180	.090	.026	.174	.088	.025	.169	.087	.025	
9.0	.176	.085	.024	.174	.085	.024	.168	.083	.024	.163	.082	.023	.159	.081	.023	
10.0	.166	.079	.022	.163	.079	.022	.158	.078	.022	.154	.076	.022	.150	.075	.022	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.182	.156	.133	.156	.134	.114	.106	.092	.079	.061	.053	.046	.020	.017	.015	
2.0	.174	.132	.096	.149	.113	.083	.102	.079	.058	.059	.046	.034	.019	.015	.011	
3.0	.166	.114	.073	.143	.099	.063	.098	.069	.044	.057	.040	.026	.018	.013	.009	
4.0	.159	.101	.057	.136	.087	.050	.094	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.151	.091	.046	.130	.079	.040	.089	.055	.028	.052	.032	.017	.017	.011	.006	
6.0	.144	.082	.039	.124	.071	.034	.085	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.137	.076	.033	.118	.066	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.061	.025	.078	.042	.018	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.7	21.2	19.9	21.4	21.6	20.0	21.6	20.3	21.8	22.0
3H	21.1	22.6	21.4	22.8	23.1	21.3	22.8	21.6	23.0	23.2
4H	21.7	23.1	22.1	23.4	23.6	21.7	23.1	22.0	23.4	23.6
6H	22.2	23.5	22.5	23.8	24.1	22.1	23.4	22.4	23.6	23.9
8H	22.4	23.6	22.7	23.9	24.2	22.2	23.5	22.6	23.8	24.0
12H	22.5	23.7	22.8	24.0	24.3	22.3	23.6	22.7	23.9	24.2
4H 2H	20.3	21.7	20.6	21.9	22.2	20.6	21.9	20.9	22.2	22.4
3H	22.0	23.2	22.3	23.5	23.8	22.0	23.3	22.4	23.6	23.9
4H	22.7	23.8	23.1	24.1	24.5	22.6	23.7	22.9	24.0	24.3
6H	23.3	24.3	23.7	24.6	25.0	23.0	24.0	23.4	24.4	24.7
8H	23.5	24.4	23.9	24.8	25.2	23.3	24.2	23.7	24.5	24.9
12H	23.7	24.5	24.1	24.9	25.3	23.4	24.3	23.9	24.7	25.1
8H 4H	22.9	23.9	23.3	24.2	24.6	22.8	23.7	23.2	24.1	24.5
6H	23.7	24.4	24.1	24.8	25.3	23.4	24.2	23.9	24.6	25.0
8H	24.0	24.7	24.4	25.1	25.5	23.7	24.4	24.2	24.9	25.3
12H	24.2	24.8	24.7	25.2	25.7	24.1	24.7	24.5	25.1	25.6
12H 4H	22.9	23.8	23.4	24.2	24.6	22.8	23.7	23.2	24.1	24.5
6H	23.7	24.4	24.2	24.8	25.3	23.5	24.2	23.9	24.6	25.1
8H	24.0	24.6	24.5	25.1	25.6	23.9	24.5	24.3	24.9	25.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.1					+ 0.2 / - 0.2				
1.5H	+ 0.1 / - 0.2					+ 0.3 / - 0.4				
2.0H	+ 0.1 / - 0.2					+ 0.3 / - 0.3				

CIE Pub.117 Corrected 3338 lm Total Lamp Luminous Flux. (8log(F/F0) = 4.2)

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	56	44	37	54	44	37	31
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	55	73	62	55	71	64	55	47
1.25	82	71	63	80	70	63	77	68	62	54
1.50	87	76	69	85	75	68	82	74	67	60
2.00	94	85	78	92	83	77	88	81	75	67
2.50	98	89	83	96	88	82	92	85	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	94	103	97	93	98	94	90	81
5.00	108	103	98	105	101	97	101	97	94	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Conical surface Flux(90deg):

1702.1 lm

%lum = 51.0%


%lamp = 51.0%

Conical surface Flux(120deg):

2524.6 lm

%lum = 75.6%


%lamp = 75.6%



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

AAI Figure




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM



C Range: 0 - 360DEG	γ Range: 0 - 90DEG
C Interval: 5.0DEG	γ Interval: 0.5DEG
Test Speed: HIGH	Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Temperature:25DEG	Humidity:50%
Operators:	Test Distance:8.600m [K=1.0000]
Test Date:2020-05-15	Remarks:

LED Avg.L Report

Test:U:120.2V I:0.1851A P:22.09W PF:0.9930 Lamp Flux:3337.7x1 lm		
NAME: LOC-14TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1155*95	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180 (65) av	8008
L_0~180 (75) av	7293
L_0~180 (85) av	6380
L_90~270 (65) av	10244
L_90~270 (75) av	10430
L_90~270 (85) av	13527
L_45 (65) av	9446
L_45 (75) av	9364
L_45 (85) av	11464

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--3

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

Range: 0 - 90DEG
Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--4

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```