


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.1V I:0.3262A P:38.93W PF:0.9936 Lamp Flux:2723.41x2 lm		
NAME: LOC-24TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Fintronx LLC	SUR.:1188*63*14mm	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 139.91 lm/W			
MODEL	5000K	Imax(cd)	1821	S/MH(C0/180)	1.25
NOMINAL POWER(W)	39	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	120-277	TOTAL FLUX(lm)	5446.8	η UP,DN(C0-180)	0.0,49.0
NOMINAL FLUX(lm)	2723.41	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,51.0
LAMPS INSIDE	2	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-23

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
5	1807	1785	1781	1791	1816	1796	1789	1791	0- 5	43.12	43.12	0.79,0.79
10	1775	1741	1742	1752	1792	1763	1758	1752	5- 10	126.9	170.0	3.12,3.12
15	1726	1688	1702	1705	1750	1720	1726	1705	10- 15	205.7	375.7	6.9,6.9
20	1661	1628	1663	1650	1691	1670	1694	1651	15- 20	277.7	653.4	12,12
25	1580	1561	1623	1587	1616	1612	1662	1591	20- 25	341.5	995.0	18.3,18.3
30	1487	1489	1526	1519	1528	1548	1568	1525	25- 30	394.4	1389	25.5,25.5
35	1383	1400	1428	1433	1426	1464	1473	1441	30- 35	432.1	1822	33.4,33.4
40	1268	1279	1331	1314	1313	1345	1378	1322	35- 40	455.5	2277	41.8,41.8
45	1145	1158	1234	1193	1191	1226	1283	1203	40- 45	465.2	2742	50.3,50.3
50	1016	1037	1136	1073	1060	1106	1189	1085	45- 50	461.7	3204	58.8,58.8
55	879.6	918.4	1023	954.3	922.6	988.0	1075	968.2	50- 55	445.5	3649	67,67
60	738.7	800.4	910.4	836.2	778.4	870.0	961.9	852.6	55- 60	416.3	4066	74.6,74.6
65	594.1	673.9	797.4	709.1	630.3	738.8	848.4	728.1	60- 65	376.6	4442	81.6,81.6
70	448.6	551.5	684.4	586.3	479.3	611.2	735.0	608.2	65- 70	328.3	4771	87.6,87.6
75	306.6	433.9	571.4	468.0	331.5	488.1	621.5	493.3	70- 75	273.9	5044	92.6,92.6
80	177.0	315.0	388.7	346.1	193.1	361.7	436.4	375.3	75- 80	210.9	5255	96.5,96.5
85	73.14	167.3	206.1	182.9	83.91	194.9	251.2	216.7	80- 85	134.8	5390	99,99
90	15.12	22.65	23.51	22.63	23.75	31.21	66.03	61.19	85- 90	56.65	5447	100,100
95									90- 95			
100									95-100			
105									100-105			
110									105-110			
115									110-115			
120									115-120			
125									120-125			
130									125-130			
135									130-135			
140									135-140			
145									140-145			
150									145-150			
155									150-155			
160									155-160			
165									160-165			
170									165-170			
175									170-175			
180									175-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-23

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.02	.98	.93	1.00	.96	.92	.96	.92	.89	.92	.89	.86	.88	.86	.84	.81
2.0	.89	.81	.75	.87	.80	.74	.83	.77	.72	.80	.75	.71	.77	.73	.69	.67
3.0	.77	.69	.62	.76	.68	.61	.73	.66	.60	.70	.64	.59	.67	.62	.58	.56
4.0	.68	.59	.52	.67	.58	.52	.64	.57	.51	.62	.56	.50	.60	.54	.50	.47
5.0	.61	.52	.45	.60	.51	.44	.58	.50	.44	.56	.49	.43	.54	.48	.43	.41
6.0	.55	.46	.39	.54	.45	.39	.52	.44	.38	.50	.43	.38	.49	.42	.38	.35
7.0	.50	.41	.34	.49	.40	.34	.47	.39	.34	.46	.39	.34	.44	.38	.33	.31
8.0	.45	.36	.31	.45	.36	.30	.43	.36	.30	.42	.35	.30	.41	.34	.30	.28
9.0	.41	.33	.27	.41	.33	.27	.40	.32	.27	.39	.32	.27	.38	.31	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.24	.23



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-23

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.338	.192	.061	.331	.189	.060	.317	.182	.058	.305	.176	.056	.294	.170	.055		
2.0	.310	.170	.052	.304	.167	.052	.292	.162	.050	.281	.158	.049	.271	.153	.048		
3.0	.283	.151	.045	.277	.148	.045	.267	.145	.044	.257	.141	.043	.248	.137	.042		
4.0	.259	.134	.040	.254	.133	.039	.244	.130	.039	.236	.127	.038	.228	.124	.038		
5.0	.237	.121	.035	.233	.120	.035	.225	.117	.034	.217	.115	.034	.210	.112	.034		
6.0	.219	.110	.031	.215	.109	.031	.208	.107	.031	.201	.104	.031	.195	.102	.030		
7.0	.203	.100	.028	.200	.100	.028	.193	.098	.028	.187	.096	.028	.181	.094	.028		
8.0	.189	.092	.026	.186	.092	.026	.180	.090	.026	.175	.089	.026	.170	.087	.025		
9.0	.177	.086	.024	.174	.085	.024	.169	.084	.024	.164	.082	.024	.159	.081	.023		
10.0	.166	.080	.022	.164	.079	.022	.159	.078	.022	.154	.077	.022	.150	.076	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.182	.156	.132	.156	.134	.114	.107	.092	.079	.061	.053	.046	.020	.017	.015	
2.0	.175	.132	.096	.150	.113	.083	.103	.079	.058	.059	.046	.034	.019	.015	.011	
3.0	.167	.114	.072	.143	.099	.063	.098	.069	.044	.057	.040	.026	.018	.013	.009	
4.0	.159	.101	.057	.137	.087	.049	.094	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.152	.091	.046	.130	.079	.040	.090	.055	.028	.052	.032	.017	.017	.011	.006	
6.0	.144	.083	.038	.124	.071	.033	.085	.050	.024	.050	.029	.014	.016	.010	.005	
7.0	.137	.076	.033	.118	.066	.028	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.061	.025	.078	.043	.017	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-23

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.9	16.5	15.2	16.7	16.9	15.9	17.5	16.2	17.7	17.9
3H	16.3	17.8	16.6	18.0	18.3	18.0	19.4	18.3	19.7	19.9
4H	16.9	18.3	17.2	18.5	18.8	19.1	20.4	19.4	20.7	21.0
6H	17.2	18.6	17.6	18.8	19.1	19.9	21.3	20.3	21.5	21.8
8H	17.3	18.6	17.7	18.9	19.2	20.3	21.6	20.6	21.8	22.1
12H	17.4	18.6	17.8	18.9	19.2	20.6	21.8	20.9	22.1	22.4
4H 2H	15.7	17.1	16.0	17.3	17.6	16.5	17.8	16.8	18.1	18.4
3H	17.3	18.5	17.7	18.8	19.2	18.8	20.0	19.1	20.3	20.6
4H	18.0	19.1	18.4	19.5	19.8	20.0	21.1	20.4	21.5	21.8
6H	18.5	19.5	18.9	19.9	20.2	21.1	22.1	21.5	22.4	22.8
8H	18.7	19.6	19.1	20.0	20.3	21.5	22.4	21.9	22.8	23.2
12H	18.7	19.6	19.2	20.0	20.4	21.9	22.7	22.3	23.1	23.5
8H 4H	18.6	19.5	19.0	19.9	20.3	20.3	21.2	20.7	21.6	22.0
6H	19.3	20.1	19.7	20.5	20.9	21.6	22.4	22.0	22.8	23.2
8H	19.5	20.2	20.0	20.7	21.1	22.1	22.8	22.6	23.3	23.7
12H	19.7	20.3	20.2	20.8	21.3	22.6	23.2	23.1	23.7	24.2
12H 4H	18.7	19.5	19.1	19.9	20.3	20.3	21.2	20.7	21.5	22.0
6H	19.5	20.2	20.0	20.6	21.1	21.6	22.3	22.1	22.8	23.2
8H	19.8	20.5	20.3	20.9	21.4	22.3	22.9	22.7	23.3	23.8
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.1				
1.5H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
2.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.3				

CIE Pub.117 Corrected 5447 lm Total Lamp Luminous Flux. (8log(F/F0) = 5.9)

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-23

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	43	37	30
0.80	66	54	46	65	53	46	63	53	46	39
1.00	74	63	55	73	62	55	71	64	54	47
1.25	81	70	63	80	69	62	77	68	61	54
1.50	86	76	68	85	75	68	81	73	67	59
2.00	93	84	77	91	83	76	88	81	75	67
2.50	97	89	82	95	88	82	91	85	80	71
3.00	101	93	87	99	92	86	94	89	84	75
4.00	105	99	94	103	97	92	98	94	90	81
5.00	108	102	98	105	100	96	100	97	93	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-23

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Conical surface Flux(90deg):

2742.2 lm

%lum = 50.3%


%lamp = 50.3%

Conical surface Flux(120deg):

4065.8 lm

%lum = 74.6%


%lamp = 74.6%



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-05-23

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

AAI Figure




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-23

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

ISOLUX DIAGRAM



C Range: 0 - 360DEG	γ Range: 0 - 90DEG
C Interval: 5.0DEG	γ Interval: 0.5DEG
Test Speed: HIGH	Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Temperature:25DEG	Humidity:50%
Operators:	Test Distance:8.600m [K=1.0000]
Test Date:2020-05-23	Remarks:

LED Avg.L Report

Test:U:120.1V I:0.3262A P:38.93W PF:0.9936 Lamp Flux:2723.41x2 lm		
NAME: LOC-24TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Fintronx LLC	SUR.:1188*63*14mm	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180 (65) av	1936
L_0~180 (75) av	1647
L_0~180 (85) av	1204
L_90~270 (65) av	2602
L_90~270 (75) av	3079
L_90~270 (85) av	3505
L_45 (65) av	2252
L_45 (75) av	2430
L_45 (85) av	2920

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-23

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-23

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-23

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-23

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--3

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-23

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--4

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-23

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```