


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.0V I:0.1840A P:21.97W PF:0.9946 Lamp Flux:1575.76x2 lm		
NAME: LOC-22TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:610*430*35mm	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 143.47 lm/W			
MODEL	3500K	I _{max} (cd)	1062	S/MH (C0/180)	1.24
NOMINAL POWER(W)	24	LOR(%)	100.0	S/MH (C90/270)	1.25
RATED VOLTAGE(V)	120-277	TOTAL FLUX(lm)	3151.5	η UP,DN(C0-180)	0.0,50.3
NOMINAL FLUX(lm)	1575.76	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.7
LAMPS INSIDE	2	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120	η down (%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
5	1056	1044	1042	1045	1058	1044	1040	1043	0- 5	25.14	25.14	0.80,0.80
10	1039	1021	1021	1024	1042	1022	1018	1019	5- 10	73.99	99.14	3.15,3.15
15	1012	993.3	1001	996.7	1017	993.6	995.9	989.9	10- 15	119.9	219.0	6.95,6.95
20	974.9	961.5	980.2	965.3	982.1	961.3	973.8	956.7	15- 20	161.8	380.9	12.1,12.1
25	929.4	925.3	959.7	929.6	938.5	925.0	951.7	919.6	20- 25	199.0	579.9	18.4,18.4
30	875.8	886.3	903.4	890.9	886.0	885.5	894.5	879.4	25- 30	229.8	809.7	25.7,25.7
35	815.8	836.4	847.1	840.9	827.0	834.9	837.3	828.5	30- 35	251.7	1061	33.7,33.7
40	749.4	766.5	790.8	771.1	761.2	765.3	780.1	758.1	35- 40	265.2	1327	42.1,42.1
45	677.5	696.3	734.5	700.9	689.6	695.1	722.9	687.3	40- 45	270.6	1597	50.7,50.7
50	601.1	626.3	678.3	630.2	613.4	624.8	665.7	616.5	45- 50	268.4	1866	59.2,59.2
55	520.6	557.1	613.5	560.5	532.6	555.4	600.0	546.7	50- 55	258.6	2124	67.4,67.4
60	436.5	488.5	548.7	490.9	447.9	486.4	534.4	477.0	55- 60	241.3	2366	75.1,75.1
65	350.5	414.0	483.9	414.5	360.8	410.4	468.7	401.3	60- 65	217.8	2583	82,82
70	263.6	341.4	419.1	340.3	272.7	336.4	403.1	328.0	65- 70	189.2	2773	88,88
75	178.9	271.5	354.3	268.6	185.3	264.7	337.5	257.1	70- 75	156.8	2929	93,93
80	101.3	199.9	240.7	195.4	106.9	192.0	229.3	185.6	75- 80	119.3	3049	96.7,96.7
85	41.41	105.6	127.1	103.3	45.76	101.4	121.2	98.15	80- 85	74.11	3123	99.1,99.1
90	8.587	13.19	13.50	13.29	13.79	12.75	13.14	12.59	85- 90	28.77	3152	100,100
95									90- 95			
100									95-100			
105									100-105			
110									105-110			
115									110-115			
120									115-120			
125									120-125			
130									125-130			
135									130-135			
140									135-140			
145									140-145			
150									145-150			
155									150-155			
160									155-160			
165									160-165			
170									165-170			
175									170-175			
180									175-180			
DEG	LUMINOUS INTENSITY:cd								UNIT:lm			

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.03	.98	.94	1.00	.96	.92	.96	.92	.89	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.75	.87	.80	.74	.83	.78	.73	.80	.75	.71	.77	.73	.69	.67
3.0	.78	.69	.62	.76	.68	.62	.73	.66	.60	.70	.64	.59	.68	.63	.58	.56
4.0	.69	.59	.52	.67	.59	.52	.65	.57	.51	.62	.56	.51	.60	.54	.50	.48
5.0	.61	.52	.45	.60	.51	.45	.58	.50	.44	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.39	.54	.45	.39	.52	.44	.39	.50	.43	.38	.49	.43	.38	.36
7.0	.50	.41	.34	.49	.40	.34	.47	.40	.34	.46	.39	.34	.44	.38	.34	.31
8.0	.45	.37	.31	.45	.36	.31	.43	.36	.30	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.27	.40	.32	.27	.39	.32	.27	.38	.32	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.335	.190	.060	.327	.187	.059	.314	.180	.058	.302	.174	.056	.290	.168	.054		
2.0	.308	.169	.052	.302	.166	.051	.290	.161	.050	.279	.156	.049	.269	.152	.048		
3.0	.281	.150	.045	.276	.148	.044	.265	.144	.044	.256	.140	.043	.247	.137	.042		
4.0	.258	.134	.039	.253	.132	.039	.243	.129	.039	.235	.126	.038	.227	.123	.038		
5.0	.237	.121	.035	.232	.119	.035	.224	.117	.034	.216	.114	.034	.209	.112	.034		
6.0	.219	.110	.031	.215	.108	.031	.207	.106	.031	.201	.104	.031	.194	.102	.030		
7.0	.203	.100	.028	.199	.099	.028	.193	.097	.028	.187	.096	.028	.181	.094	.028		
8.0	.189	.092	.026	.186	.092	.026	.180	.090	.026	.174	.088	.025	.169	.087	.025		
9.0	.177	.085	.024	.174	.085	.024	.169	.083	.024	.164	.082	.023	.159	.081	.023		
10.0	.166	.080	.022	.163	.079	.022	.159	.078	.022	.154	.077	.022	.150	.075	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.182	.156	.132	.156	.134	.114	.107	.092	.079	.061	.053	.046	.020	.017	.015	
2.0	.174	.132	.096	.149	.113	.083	.102	.079	.058	.059	.046	.034	.019	.015	.011	
3.0	.167	.114	.073	.143	.099	.063	.098	.069	.044	.057	.040	.026	.018	.013	.009	
4.0	.159	.101	.057	.136	.087	.050	.094	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.151	.091	.046	.130	.079	.040	.090	.055	.028	.052	.032	.017	.017	.011	.006	
6.0	.144	.083	.038	.124	.071	.033	.085	.050	.024	.050	.029	.014	.016	.010	.005	
7.0	.137	.076	.033	.118	.066	.028	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.061	.025	.078	.043	.017	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.3	17.9	16.6	18.1	18.3	17.3	18.9	17.6	19.1	19.3
3H	17.7	19.2	18.0	19.4	19.7	19.5	20.9	19.8	21.2	21.4
4H	18.3	19.7	18.6	19.9	20.2	20.6	22.0	20.9	22.2	22.5
6H	18.6	19.9	19.0	20.2	20.5	21.5	22.8	21.9	23.1	23.4
8H	18.7	20.0	19.1	20.3	20.6	21.9	23.1	22.2	23.4	23.7
12H	18.8	20.0	19.1	20.3	20.6	22.1	23.4	22.5	23.7	24.0
4H 2H	17.1	18.5	17.4	18.8	19.0	17.9	19.3	18.2	19.6	19.8
3H	18.8	20.0	19.1	20.3	20.6	20.3	21.5	20.7	21.8	22.1
4H	19.5	20.6	19.8	20.9	21.2	21.6	22.7	22.0	23.0	23.4
6H	20.0	21.0	20.4	21.3	21.7	22.7	23.7	23.1	24.0	24.4
8H	20.1	21.0	20.5	21.4	21.8	23.1	24.1	23.5	24.4	24.8
12H	20.2	21.1	20.6	21.4	21.9	23.5	24.3	23.9	24.7	25.1
8H 4H	20.1	21.0	20.5	21.4	21.8	21.9	22.8	22.3	23.2	23.6
6H	20.8	21.6	21.2	22.0	22.4	23.2	24.0	23.6	24.4	24.8
8H	21.1	21.8	21.5	22.2	22.6	23.8	24.5	24.2	24.9	25.3
12H	21.3	21.9	21.7	22.3	22.8	24.3	24.9	24.7	25.3	25.8
12H 4H	20.2	21.1	20.6	21.4	21.9	21.9	22.8	22.3	23.1	23.5
6H	21.0	21.7	21.5	22.2	22.6	23.3	24.0	23.7	24.4	24.9
8H	21.4	22.0	21.9	22.5	22.9	23.9	24.5	24.4	25.0	25.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.2					+ 0.1 / - 0.2				
2.0H	+ 0.1 / - 0.2					+ 0.2 / - 0.3				

CIE Pub.117 Corrected 3152 lm Total Lamp Luminous Flux. (8log(F/F0) = 4.0)

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	56	44	37	54	44	37	30
0.80	66	54	47	65	54	46	63	53	46	39
1.00	74	63	55	73	62	55	71	64	54	47
1.25	81	70	63	80	70	63	77	68	62	54
1.50	86	76	69	85	75	68	82	73	67	59
2.00	93	84	78	92	83	77	88	81	75	67
2.50	97	89	83	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	95	89	84	76
4.00	105	99	94	103	97	93	98	94	90	81
5.00	108	102	98	105	101	97	101	97	93	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004				Suspended				SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Conical surface Flux(90deg):

1597.3 lm

%lum = 50.7%


%lamp = 50.7%

Conical surface Flux(120deg):

2365.6 lm

%lum = 75.1%


%lamp = 75.1%



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

AAI Figure




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

ISOLUX DIAGRAM



C Range: 0 - 360DEG	γ Range: 0 - 90DEG
C Interval: 5.0DEG	γ Interval: 0.5DEG
Test Speed: HIGH	Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Temperature:25DEG	Humidity:50%
Operators:	Test Distance:8.600m [K=1.0000]
Test Date:2020-04-21	Remarks:

LED Avg.L Report

Test:U:120.0V I:0.1840A P:21.97W PF:0.9946 Lamp Flux:1575.76x2 lm		
NAME: LOC-22TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:610*430*35mm	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180 (65) av	2697
L_0~180 (75) av	2256
L_0~180 (85) av	1603
L_90~270 (65) av	3612
L_90~270 (75) av	4283
L_90~270 (85) av	4566
L_45 (65) av	3110
L_45 (75) av	3288
L_45 (85) av	3755

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--3

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--4

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21

```

Range: 0 - 90DEG
Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```