


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.2V I:0.1894A P:22.61W PF:0.9934 Lamp Flux:3251.59x1 lm		
NAME: LOC-14TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1155*95	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 143.82 lm/W			
MODEL		I _{max} (cd)	1107	S/MH (C0/180)	1.23
NOMINAL POWER(W)	24	LOR(%)	100.0	S/MH (C90/270)	1.34
RATED VOLTAGE(V)	120-277	TOTAL FLUX(lm)	3251.6	η UP,DN(C0-180)	0.0,45.5
NOMINAL FLUX(lm)	3251.59	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,54.5
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120	η down (%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-05-15

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
5	1100	1082	1078	1084	1102	1096	1095	1095	0- 5	26.22	26.22	0.81,0.81
10	1081	1053	1049	1056	1085	1080	1083	1077	5- 10	77.21	103.4	3.18,3.18
15	1050	1017	1020	1022	1057	1058	1072	1054	10- 15	125.1	228.6	7.03,7.03
20	1009	977.2	990.5	982.8	1018	1031	1060	1025	15- 20	169.0	397.5	12.2,12.2
25	958.6	933.1	961.4	939.9	968.9	999.0	1048	992.7	20- 25	207.7	605.3	18.6,18.6
30	899.4	885.8	899.5	893.7	911.1	963.4	998.7	956.4	25- 30	239.8	845.1	26,26
35	833.1	828.4	837.6	837.0	846.0	916.2	949.1	908.6	30- 35	262.7	1108	34.1,34.1
40	760.8	753.3	775.7	762.3	774.5	848.3	899.5	840.0	35- 40	277.1	1385	42.6,42.6
45	684.4	678.3	713.8	687.2	698.4	780.0	850.0	771.1	40- 45	283.1	1668	51.3,51.3
50	604.3	603.9	651.9	612.7	618.5	712.1	800.4	702.8	45- 50	281.5	1949	60,60
55	522.7	531.1	551.8	539.5	536.0	645.6	721.4	636.0	50- 55	271.4	2221	68.3,68.3
60	439.9	456.6	451.8	464.0	452.6	578.0	642.4	568.2	55- 60	251.1	2472	76,76
65	357.8	361.5	351.8	365.2	369.0	492.6	563.4	483.7	60- 65	223.2	2695	82.9,82.9
70	277.4	270.0	251.8	269.8	286.7	410.8	484.4	403.0	65- 70	189.5	2885	88.7,88.7
75	199.3	181.8	151.7	177.6	205.7	332.6	405.4	326.0	70- 75	151.5	3036	93.4,93.4
80	125.8	102.3	105.8	94.88	130.7	252.7	288.1	247.4	75- 80	111.4	3147	96.8,96.8
85	57.65	57.81	59.94	53.90	61.59	146.4	170.8	142.2	80- 85	71.51	3219	99,99
90	8.823	13.93	14.04	13.60	14.18	42.02	53.48	38.72	85- 90	32.58	3252	100,100
95									90- 95			
100									95-100			
105									100-105			
110									105-110			
115									110-115			
120									115-120			
125									120-125			
130									125-130			
135									130-135			
140									135-140			
145									140-145			
150									145-150			
155									150-155			
160									155-160			
165									160-165			
170									165-170			
175									170-175			
180									175-180			
DEG	LUMINOUS INTENSITY:cd								UNIT:lm			

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.03	.98	.94	1.01	.96	.93	.96	.93	.90	.92	.89	.87	.89	.86	.84	.82
2.0	.89	.82	.76	.87	.81	.75	.84	.78	.73	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.69	.63	.76	.68	.62	.73	.67	.61	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.61	.52	.45	.60	.52	.45	.58	.50	.45	.56	.49	.44	.54	.48	.44	.41
6.0	.55	.46	.40	.54	.46	.39	.52	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.35	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.330	.188	.059	.323	.184	.059	.310	.178	.057	.297	.172	.055	.286	.166	.053	
2.0	.304	.167	.051	.298	.164	.051	.286	.159	.049	.275	.155	.048	.265	.150	.047	
3.0	.279	.148	.044	.273	.146	.044	.263	.142	.043	.253	.139	.043	.244	.135	.042	
4.0	.256	.133	.039	.251	.131	.039	.242	.128	.038	.233	.125	.038	.225	.122	.037	
5.0	.235	.120	.035	.231	.119	.035	.223	.116	.034	.215	.113	.034	.208	.111	.033	
6.0	.218	.109	.031	.214	.108	.031	.206	.106	.031	.200	.104	.030	.193	.102	.030	
7.0	.202	.100	.028	.199	.099	.028	.192	.097	.028	.186	.095	.028	.180	.094	.028	
8.0	.188	.092	.026	.185	.091	.026	.179	.090	.026	.174	.088	.025	.169	.087	.025	
9.0	.176	.085	.024	.173	.084	.024	.168	.083	.024	.163	.082	.023	.159	.081	.023	
10.0	.165	.079	.022	.163	.079	.022	.158	.077	.022	.154	.076	.022	.150	.075	.022	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.182	.156	.133	.155	.134	.114	.106	.092	.079	.061	.053	.046	.020	.017	.015	
2.0	.174	.132	.096	.149	.113	.083	.102	.079	.058	.059	.046	.034	.019	.015	.011	
3.0	.166	.114	.073	.142	.099	.063	.098	.069	.044	.056	.040	.026	.018	.013	.009	
4.0	.158	.101	.057	.136	.087	.050	.094	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.151	.091	.046	.130	.079	.040	.089	.055	.029	.052	.032	.017	.017	.011	.006	
6.0	.144	.082	.039	.123	.071	.034	.085	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.137	.076	.033	.118	.065	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.061	.025	.077	.042	.018	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.7	21.2	19.9	21.4	21.6	20.0	21.6	20.3	21.8	22.0
3H	21.2	22.6	21.5	22.8	23.1	21.3	22.8	21.6	23.0	23.2
4H	21.8	23.1	22.1	23.4	23.7	21.7	23.1	22.0	23.3	23.6
6H	22.2	23.5	22.6	23.8	24.1	22.0	23.3	22.4	23.6	23.9
8H	22.4	23.6	22.7	23.9	24.2	22.2	23.4	22.5	23.7	24.0
12H	22.5	23.7	22.9	24.0	24.3	22.3	23.5	22.7	23.8	24.1
4H 2H	20.3	21.7	20.6	22.0	22.2	20.6	22.0	20.9	22.2	22.5
3H	22.0	23.2	22.3	23.5	23.8	22.1	23.3	22.4	23.6	23.9
4H	22.7	23.8	23.1	24.2	24.5	22.6	23.7	22.9	24.0	24.3
6H	23.3	24.3	23.7	24.7	25.0	23.0	24.0	23.4	24.3	24.7
8H	23.5	24.5	24.0	24.8	25.2	23.2	24.1	23.6	24.5	24.9
12H	23.7	24.5	24.1	24.9	25.3	23.4	24.3	23.8	24.6	25.1
8H 4H	23.0	23.9	23.4	24.2	24.6	22.8	23.7	23.2	24.1	24.5
6H	23.7	24.5	24.1	24.9	25.3	23.4	24.2	23.8	24.6	25.0
8H	24.0	24.7	24.4	25.1	25.5	23.7	24.4	24.2	24.8	25.3
12H	24.2	24.8	24.7	25.3	25.7	24.0	24.6	24.5	25.0	25.5
12H 4H	23.0	23.8	23.4	24.2	24.6	22.8	23.7	23.2	24.0	24.5
6H	23.7	24.4	24.2	24.8	25.3	23.5	24.1	23.9	24.6	25.0
8H	24.1	24.7	24.5	25.1	25.6	23.8	24.4	24.3	24.9	25.3
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.1					+ 0.2 / - 0.2				
1.5H	+ 0.1 / - 0.2					+ 0.3 / - 0.4				
2.0H	+ 0.1 / - 0.2					+ 0.3 / - 0.3				

CIE Pub.117 Corrected 3252 lm Total Lamp Luminous Flux. (8log(F/F0) = 4.1)

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	37	55	44	37	31
0.80	66	54	47	65	54	47	64	53	46	39
1.00	75	63	56	73	63	55	71	64	55	48
1.25	82	71	63	80	70	63	78	69	62	55
1.50	87	77	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	68
2.50	98	90	83	96	88	82	92	86	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	94	103	98	93	99	94	90	81
5.00	108	103	98	105	101	97	101	97	94	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Conical surface Flux(90deg):

1668 lm

%lum = 51.3%


%lamp = 51.3%

Conical surface Flux(120deg):

2472 lm

%lum = 76.0%


%lamp = 76.0%



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

AAI Figure




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-05-15

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.2V I:0.1894A P:22.61W PF:0.9934 Lamp Flux:3251.59x1 lm		
NAME: LOC-14TRKT-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:1155*95	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180 (65) av	7838
L_0~180 (75) av	7132
L_0~180 (85) av	6236
L_90~270 (65) av	9870
L_90~270 (75) av	9811
L_90~270 (85) av	12066
L_45 (65) av	9183
L_45 (75) av	8964
L_45 (85) av	10467

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--3

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--4

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-05-15

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```