


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.0V I:0.1837A P:21.94W PF:0.9946 Lamp Flux:1614.25x2 lm		
NAME: LOC-22TROF-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:580*145	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 147.18 lm/W			
MODEL		I _{max} (cd)	1087	S/MH (C0/180)	1.24
NOMINAL POWER(W)	24	LOR(%)	100.0	S/MH (C90/270)	1.25
RATED VOLTAGE(V)	120-277	TOTAL FLUX(lm)	3228.5	η UP,DN(C0-180)	0.0,50.4
NOMINAL FLUX(lm)	1614.25	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.6
LAMPS INSIDE	2	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120	η down (%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
5	1080	1068	1066	1070	1082	1068	1064	1067	0- 5	25.72	25.72	0.80,0.80
10	1062	1045	1045	1048	1066	1045	1041	1042	5- 10	75.70	101.4	3.14,3.14
15	1034	1017	1025	1020	1041	1016	1018	1012	10- 15	122.7	224.1	6.94,6.94
20	997.3	984.4	1004	988.8	1005	983.1	995.2	978.0	15- 20	165.6	389.7	12.1,12.1
25	950.8	947.9	983.5	952.8	960.4	946.1	972.4	940.0	20- 25	203.7	593.4	18.4,18.4
30	896.7	908.5	926.4	913.3	907.2	905.7	913.8	898.9	25- 30	235.2	828.6	25.7,25.7
35	835.1	857.8	869.2	862.4	847.1	854.1	855.3	846.7	30- 35	257.7	1086	33.6,33.6
40	767.1	786.7	812.1	791.0	780.2	782.6	796.7	774.5	35- 40	271.6	1358	42.1,42.1
45	693.7	715.0	754.9	719.2	706.9	711.0	738.1	701.9	40- 45	277.2	1635	50.6,50.6
50	615.6	643.3	697.8	647.3	629.0	639.2	679.5	629.4	45- 50	274.9	1910	59.2,59.2
55	533.1	572.8	631.3	575.8	546.0	568.3	612.4	557.9	50- 55	265.0	2175	67.4,67.4
60	447.3	502.5	564.8	504.5	460.0	497.7	545.3	486.7	55- 60	247.4	2422	75,75
65	358.9	426.1	498.3	426.4	370.6	420.1	478.3	409.2	60- 65	223.3	2646	81.9,81.9
70	269.9	351.7	431.8	350.1	280.2	344.7	411.2	334.4	65- 70	194.0	2840	88,88
75	183.0	279.7	365.3	276.4	190.6	271.6	344.1	261.9	70- 75	160.9	3001	92.9,92.9
80	103.4	206.0	248.2	201.4	110.3	197.2	233.9	188.8	75- 80	122.4	3123	96.7,96.7
85	42.05	108.7	131.0	106.4	47.27	104.2	123.6	99.87	80- 85	76.05	3199	99.1,99.1
90	8.785	13.50	13.81	13.59	14.11	13.02	13.39	12.84	85- 90	29.50	3229	100,100
95									90- 95			
100									95-100			
105									100-105			
110									105-110			
115									110-115			
120									115-120			
125									120-125			
130									125-130			
135									130-135			
140									135-140			
145									140-145			
150									145-150			
155									150-155			
160									155-160			
165									160-165			
170									165-170			
175									170-175			
180									175-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.03	.98	.94	1.00	.96	.92	.96	.92	.89	.92	.89	.86	.88	.86	.84	.82
2.0	.89	.81	.75	.87	.80	.74	.83	.78	.73	.80	.75	.71	.77	.73	.69	.67
3.0	.78	.69	.62	.76	.68	.62	.73	.66	.60	.70	.64	.59	.67	.63	.58	.56
4.0	.68	.59	.52	.67	.59	.52	.65	.57	.51	.62	.56	.51	.60	.54	.50	.48
5.0	.61	.52	.45	.60	.51	.45	.58	.50	.44	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.39	.54	.45	.39	.52	.44	.39	.50	.43	.38	.49	.43	.38	.36
7.0	.50	.41	.34	.49	.40	.34	.47	.40	.34	.46	.39	.34	.44	.38	.33	.31
8.0	.45	.37	.31	.45	.36	.31	.43	.36	.30	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.27	.40	.32	.27	.39	.32	.27	.38	.32	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.335	.190	.060	.328	.187	.059	.314	.180	.058	.302	.174	.056	.291	.168	.054		
2.0	.308	.169	.052	.302	.166	.051	.290	.161	.050	.279	.156	.049	.269	.152	.048		
3.0	.282	.150	.045	.276	.148	.044	.265	.144	.044	.256	.140	.043	.247	.137	.042		
4.0	.258	.134	.039	.253	.132	.039	.243	.129	.039	.235	.126	.038	.227	.123	.038		
5.0	.237	.121	.035	.232	.119	.035	.224	.117	.034	.217	.114	.034	.209	.112	.034		
6.0	.219	.110	.031	.215	.109	.031	.207	.106	.031	.201	.104	.031	.194	.102	.030		
7.0	.203	.100	.028	.199	.099	.028	.193	.097	.028	.187	.096	.028	.181	.094	.028		
8.0	.189	.092	.026	.186	.092	.026	.180	.090	.026	.175	.088	.026	.169	.087	.025		
9.0	.177	.085	.024	.174	.085	.024	.169	.083	.024	.164	.082	.023	.159	.081	.023		
10.0	.166	.080	.022	.163	.079	.022	.159	.078	.022	.154	.077	.022	.150	.075	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.182	.156	.132	.156	.134	.114	.107	.092	.079	.061	.053	.046	.020	.017	.015	
2.0	.174	.132	.096	.149	.113	.083	.102	.079	.058	.059	.046	.034	.019	.015	.011	
3.0	.167	.114	.073	.143	.099	.063	.098	.069	.044	.057	.040	.026	.018	.013	.009	
4.0	.159	.101	.057	.136	.087	.050	.094	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.151	.091	.046	.130	.079	.040	.090	.055	.028	.052	.032	.017	.017	.011	.006	
6.0	.144	.083	.038	.124	.071	.033	.085	.050	.024	.050	.029	.014	.016	.010	.005	
7.0	.137	.076	.033	.118	.066	.028	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.061	.025	.078	.043	.017	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	20.9	22.5	21.2	22.7	22.9	22.0	23.6	22.3	23.8	24.0
3H	22.4	23.8	22.7	24.1	24.3	24.2	25.6	24.5	25.9	26.1
4H	22.9	24.3	23.2	24.6	24.8	25.3	26.7	25.6	26.9	27.2
6H	23.3	24.6	23.6	24.9	25.1	26.2	27.5	26.5	27.8	28.1
8H	23.4	24.6	23.7	24.9	25.2	26.6	27.8	26.9	28.1	28.4
12H	23.4	24.6	23.8	24.9	25.2	26.8	28.0	27.2	28.3	28.6
4H 2H	21.8	23.2	22.1	23.4	23.7	22.6	24.0	22.9	24.2	24.5
3H	23.4	24.6	23.8	24.9	25.3	25.0	26.2	25.3	26.5	26.8
4H	24.1	25.2	24.5	25.6	25.9	26.3	27.4	26.6	27.7	28.0
6H	24.6	25.6	25.0	26.0	26.3	27.4	28.4	27.8	28.7	29.1
8H	24.8	25.7	25.2	26.1	26.5	27.8	28.7	28.2	29.1	29.5
12H	24.8	25.7	25.3	26.1	26.5	28.2	29.0	28.6	29.4	29.8
8H 4H	24.7	25.7	25.1	26.0	26.4	26.6	27.5	27.0	27.9	28.2
6H	25.5	26.2	25.9	26.6	27.1	27.9	28.7	28.3	29.1	29.5
8H	25.7	26.4	26.2	26.9	27.3	28.5	29.2	28.9	29.6	30.0
12H	25.9	26.5	26.4	27.0	27.4	28.9	29.5	29.4	30.0	30.5
12H 4H	24.9	25.7	25.3	26.1	26.5	26.6	27.4	27.0	27.8	28.2
6H	25.7	26.4	26.2	26.8	27.3	28.0	28.7	28.4	29.1	29.5
8H	26.1	26.7	26.5	27.1	27.6	28.6	29.2	29.1	29.6	30.1
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.2					+ 0.1 / - 0.2				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117 Corrected 3229 lm Total Lamp Luminous Flux. (8log(F/F0) = 4.1)

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	44	37	30
0.80	66	54	47	65	54	46	63	53	46	39
1.00	74	63	55	73	62	55	71	64	54	47
1.25	81	70	63	80	70	63	77	68	62	54
1.50	86	76	69	85	75	68	82	73	67	59
2.00	93	84	77	91	83	77	88	81	75	67
2.50	97	89	83	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	95	89	84	76
4.00	105	99	94	103	97	93	98	94	90	81
5.00	108	102	98	105	101	96	101	97	93	84
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity: 50%
 Test Distance: 8.600m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Conical surface Flux(90deg):

1635.1 lm

%lum = 50.6%


%lamp = 50.6%

Conical surface Flux(120deg):

2422.4 lm

%lum = 75.0%


%lamp = 75.0%



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

AAI Figure




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

ISOLUX DIAGRAM



C Range: 0 - 360DEG	γ Range: 0 - 90DEG
C Interval: 5.0DEG	γ Interval: 0.5DEG
Test Speed: HIGH	Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Temperature:25DEG	Humidity:50%
Operators:	Test Distance:8.600m [K=1.0000]
Test Date:2020-04-21	Remarks:

LED Avg.L Report

Test:U:120.0V I:0.1837A P:21.94W PF:0.9946 Lamp Flux:1614.25x2 lm		
NAME: LOC-22TROF-DMWMCCT	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:580*145	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180 (65) av	10262
L_0~180 (75) av	8583
L_0~180 (85) av	6093
L_90~270 (65) av	13738
L_90~270 (75) av	16297
L_90~270 (85) av	17369
L_45 (65) av	11830
L_45 (75) av	12516
L_45 (85) av	14299

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
 Humidity:50%
 Test Distance:8.600m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

γ Range: 0 - 90DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity: 50%
Test Distance: 8.600m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--2

UNIT: cd

[illegible]

```
C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2020-04-21
```

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--3

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--4

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2020-04-21

```

γ Range: 0 - 90DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.290
Humidity:50%
Test Distance:8.600m [K=1.0000]
Remarks:

```