

LED BR Bulb Series

BR20



BR30



BR40



FEATURES

- Energy efficient, up to 80% less energy than halogen alternatives
- Durable
- Solid state lighting technology that reduces lighting service and maintenance
- 25,000 hours lifetime

SUITABLE APPLICATIONS

- Track Lighting
- Recessed Ceiling Lighting
- Retail Display Lighting
- General Household Light Fixtures

CONSTRUCTION:

Aluminum housing. Frosted lens. E26 base.

ELECTRICAL:

120V input. Dimmable. -20°C to 50°C, -4°F to 104°F

OPTICAL SYSTEM:

- BR20: 110° beam angle.
- BR30: 105° beam angle.
- BR40: 105° beam angle.

WARRANTY:

3-year limited warranty. Actual performance may differ as a result of end-user environment and application.



MODEL NUMBER	WATTAGE	LUMENS	EFFICACY	CRI	POWER FACTOR	REPLACES
BR20-50WE-7WD50K	7W	525LM	70LM/W	83	0.9	50W
BR30-65WE-12WD27K **	12W	760LM	63.3LM/W	85	0.9	65W
BR30-75WE-13.5WD27K **	13.5W	938LM	70LM/W	81	0.9	75W
BR40-75WE-15WD27K **	15W	950LM	63.3LM/W	85	0.9	75W
BR40-90WE-17WD27K **	17W	1,260LM	70LM/W	81	0.9	90W
BR40-90WE-17WD50K	17W	1,260LM	74.1LM/W	83	0.9	90W

** = UL listed only

MODEL	QUANTITY	SIZE
BR20-50WE-7WD50K	1	3.86" x 2.64"
BR30-65WE-12WD27K	1	5.19" x 3.74"
BR30-75WE-13.5WD27K	1	5.19" x 3.74"
BR40-75WE-15WD27K	1	6.5" x 5.12"
BR40-90WE-17WD27K	1	6.5" x 5.12"
BR40-90WE-17WD50K	1	6.5" x 5.12"