

LED External Tube Series



FEATURES

- Single ended Type C
- Wide beam full directional lighting
- IP40 rated
- Low thermal decay & maintenance
- No Mercury
- 50,000 hours lifetime

SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Office Buildings

CONSTRUCTION:

Glass body

OPTICAL SYSTEM:

120° beam angle

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

Available as 120-277V input. -20°C to 50°C, -4°F to 122°F

INSTALLATION & MOUNTING:

Type C single ended.

CONTROLS & DIMMING:

Non-dimming.

MODEL NUMBER	WATTAGE	LUMENS	EFFICACY	CRI	POWER FACTOR	THD	REPLACES
LOD-EXT82FD-10W40KF-1	10W	1,258.3LM	123.3LM/W	82.5	0.91	12.6%	25W
LOD-EXT82FD-10W50KF-1	10W	1,311.1LM	129.8LM/W	82.7	0.92	13.2%	25W
LOD-EXT84FD-15W50KF-1	15W	1,919.4LM	127.9LM/W	82.4	0.92	13.4%	32W