

2FT 8.5W Plug & Play Tube



FEATURES

- IP40 rated
- No Mercury or UV
- Low thermal decay
- 50,000 hours lifetime
- NSF rated for splash zone and non-food zone

SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Schools
- Hospitals
- Office Buildings

CONSTRUCTION:

Glass body with frosted lens.

OPTICAL SYSTEM:

270° beam angle

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

AC110-277V input. -20°C to 50°C, -4°F to 122°F.

INSTALLATION & MOUNTING:

Double ended Type A. Single ended Type B.

CONTROLS & DIMMING:

Non dimming.

NSF Model Numbers:

- LOC-2FTT8GP-8.5W40K
- LOC-2FTT8GP-8.5W50K



MODEL NUMBER	WATTAGE	LUMENS	EFFICACY	CRI	POWER FACTOR	THD	REPLACES
LOD-GDMT82F-8.5W40KF	8.5W	1,150LM	136LM/W	80	0.9	10%	15W – 20W
LOD-GDMT82F-8.5W50KF	8.5W	1,150LM	136LM/W	80	0.9	10%	15W – 20W