LEDone®

8 Foot

60W / 80W / 100W

Date: _____ Location: _

Product:

Project:

Quantity: ____ Catalog #:

LED LOC-8FTTPVT Multi Wattage Multi CCT Vapor Tight Light (Motion Sensor Option)

CONSTRUCTION:

PC housing and white cover.

OPTICAL SYSTEM:

Seoul 2835 LED chips. 110° beam angle.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL: 120-277V input standard. -20°C to 40°C, -4°F to 104°F

INSTALLATION & MOUNTING: Surface mount.

CONTROLS & DIMMING: 0-10V dimming comes standard.

FEATURES

- Default Wattage:
 0 8FT 100W
 - Default CCT: 5,000K
- IP65 rated
- NSF rated for splash zone and nonfood zone
 - UL 1598 suitable for wet location
- 50,000 hours lifetime

SUITABLE APPLICATIONS

- Warehouses
- Factories
- Garage
- Parking lot



DLC Product ID:

• LOC-8FTTPVT-MW(60/80/100)MCCT(35/40/50)D – S-V4ZNIE





OPTIONAL ACCESSORIES:





.

Sensor

Note: If you would like to add an emergency battery or a motion sensor to other models, please inform your sales representative **at the time of placing an order**. This will need to be done at the factory. ******additional cost

LED LOC-8FTTPVT Multi Wattage Multi CCT Vapor Tight Light

LOC-8FTTPVT-MW(60/80/100)MCCT(35/40/50)D

LEDone[®]

2.42″

0

2.61″ 66.4mm

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
60W	3500K / 4000K / 5000K	6,865.2LM	114.42LM/W	120-277V	80	0.9	20%	
80W	3500K / 4000K / 5000K	9,153.6LM	114.42LM/W	120-277V	80	0.9	20%	
100W	3500K / 4000K / 5000K	11,442LM	114.42LM/W	120-277V	80	0.9	20%	

8FT

92.82" 2357.628mm

MODEL	QUANTITY	WEIGHT	UPC CODE
LOC-8FTTPVT-MW(60/80/100)MCCT(35/40/50)D	1	lbs	00810050942225

Phone: (844) LEDONE6 | Fax: 1-510-217-9461 | Web: www.ledonecorp.com